

Technical Data Radon Scout Home

Radon measurement											
Principle of operation	Silicon detector and Alpha spectroscopy										
Range	0Bq/m ³ ... 1,000,000Bq/m ³										
Accuracy	< 2%										
Sensitivity	5.52cph/(kB/m ³)										
Stat. Error (1σ)	<table border="1"> <tr> <td>1 week @ 300Bq/m³</td> <td>6%</td> </tr> <tr> <td>1 month @ 300Bq/m³</td> <td>3%</td> </tr> <tr> <td>1 week @ 100Bq/m³</td> <td>10%</td> </tr> <tr> <td>1 month @ 100Bq/m³</td> <td>5%</td> </tr> <tr> <td>24 hours @ 300Bq/m³</td> <td>15%</td> </tr> </table>	1 week @ 300Bq/m ³	6%	1 month @ 300Bq/m ³	3%	1 week @ 100Bq/m ³	10%	1 month @ 100Bq/m ³	5%	24 hours @ 300Bq/m ³	15%
1 week @ 300Bq/m ³	6%										
1 month @ 300Bq/m ³	3%										
1 week @ 100Bq/m ³	10%										
1 month @ 100Bq/m ³	5%										
24 hours @ 300Bq/m ³	15%										
Humidity											
Range	0%rH ... 100%rH										
Accuracy	< 4.5%rH (3% typ.) for 20%rH ... 80%rH										
Temperature											
Range	-40°C ... 120°C										
Accuracy	< 0.4°C (0.3°C typ.) for 5°C ... 60°C										
Pressure (Radon Scout Home – P)											
Range	760mbar ... 1200mbar										
Accuracy	< 0.5% FSO										
CO2 (Radon Scout Home CO2)											
Principle of operation	Non dispersive infrared (NDIR)										
Range	0ppm ... 5000ppm (0% to 0.5%)										
Accuracy	< 5% ± 50ppm										
Response time	10min										
Remark	CO2 sensor works only when instrument is powered through USB connector (computer, AC/DC adapter, power bank); measurement of other parameters is not affected Automatic calibration with respect to outdoor CO2 level										
Instrument											
Environmental conditions	-10°C ... 50°C 0%rH ... 99%rH no condensation										
Power supply	2 x AAA battery or USB socket Battery operation approx. 5 ... 6 month Low battery indication by red LED Short time buffering of real time clock during battery replacement										
Display	Alpha numeric LCD with bright backlight Units can be changed between SI and US style English, German and Spanish versions available Radon average since start of a measurement series Radon average of previous 24 hours Temperature, rel. humidity Bar. Pressure (Radon Scout Home – P only) CO2 concentration (Radon Scout Home – CO2 only) Battery voltage (Radon Scout Home – P/CO2 only) Date and Time										
Data storage	Non-volatile memory with circular structure for 16383 data records in any number of test series										

	Saves all parameters including tilt detection each four hours
Interface	USB (mini USB socket)
Alert indication	Red backlight will be lighted if the CO2 concentration exceeds the threshold of 1000ppm (Radon Scout Home – CO2 only)
Operation	Slide switch to start/stop sampling Button to toggle display page and backlight
Software	Radon Vision
Dimensions	80mm x 96mm x 44mm
Weight	140g including batteries
Accessory	USB cable (incl. for all models) AC/DC adapter (incl. for models with pressure or CO2 sensor) Power bank (option for mains power independent operation with CO2 sensor) Factory calibration with certificate (option) DKD calibration with certificate (option)